


Date : **September 8, 2020**
 Quotation No. : **0227-09-2020**

REQUEST FOR QUOTATION

 Company Name

 Address

Please quote your lowest price on the item/s listed below, stating the shortest time of delivery and submit your quotation duly signed by your representative not later than _____


RANDY C. MABANA
 Head, BAC Secretariat

- NOTE :
1. ALL ENTRIES MUST BE TYPEWRITTEN OR PRINTED LEGIBLY
 2. DELIVERY PERIOD WITHIN 15 CALENDAR DAYS
 3. WARRANTY SHALL BE FOR A PERIOD OF SIX (6) MONTHS FOR SUPPLIES & MATERIALS, ONE (1) YEAR FOR EQUIPMENT, FROM DATE OF ACCEPTANCE BY THE PROCURING ENTITY
 4. PRICE VALIDITY SHALL BE FOR A PERIOD OF 30 CALENDAR DAYS
 5. PHIL-GEPS REGISTRATION CERTIFICATE SHALL BE ATTACHED UPON SUBMISSION OF THE QUOTATION
 6. BIDDERS SHALL SUBMIT ORIGINAL BROCHURES SHOWING CERTIFICATIONS OF THE PRODUCT BEING OFFERED

ITEM NO.	ITEMS/DESCRIPTIONS	QTY./ UNIT	UNIT PRICE	TOTAL PRICE
1	Indoor Dual Band Wireless Access Point	20 Units	P_____	P_____
2	Back-UPS	30 Units	P_____	P_____
3	Printserver wireless/switch	3 Units	P_____	P_____
4	USB Headset with Noise Cancelling Mic	25 Units	P_____	P_____
5	8 TB External Hard Drive	4 Units	P_____	P_____
6	USB SATA III Hard Drive Adapter Cable	2 Pcs.	P_____	P_____
7	Wireless Mouse	20 Pcs.	P_____	P_____
8	Wireless Keyboard	10 Pcs.	P_____	P_____
9	16 Port Gigabit Switch	2 Units	P_____	P_____
10	24 Port Gigabit Switch	2 Units	P_____	P_____
11	24 Port Managed Gigabit PoE+ Switch	3 Units	P_____	P_____
ABC: P612,450.00 Note: Please see attached for technical specifications. Bidders must submit the following requirements: <ol style="list-style-type: none"> 1. DTI/SEC Registration Certificate 2. Mayor's Permit 3. PHILGEPS Certificate of Registration 4. BIR Certificate of Registration 				

Brand : _____
 Delivery Period : _____
 Warranty : _____
 Price Validity : _____

After having carefully read and accepted your Request for Quotation, I/We quote you on the item at prices noted above.

 Printed Name/Signature

 Tel. No./Cellphone No.

 e-mail address

 Date

6. USB 3.0 TO SATA III HARD DRIVE ADAPTER CABLE

1. Adapter SATA III USB 3.0 Cable External Hard Drive USB to Serial ATA 22pin Converter Hard Disk 6 Gbps for 2.5" HDD/SSD
2. Connects any standard 2.5 inch SATA Hard Drive or Solid State Drive (SSD) to a computer through USB 3.0 ports. It's a ideal for you to backup files or upgrade your notebook hard driver.
3. SATA 3 specification Support speed up to 6Gbps;
4. Easy and quick access to external storage;
5. LED activity indicator;
6. Fully compatible with USB 3.0 and backwards compatible with USB 2.0/1.1;
7. Plug and play,hot-swapping;
8. Compatible with Windows XP, 7, 8,98, ME, Vista, Windows 10 and 2000 Mac OS 8.6. 9. Compliance with Serial ATA Specification Revision 2.6.

7. 16 PORT GIGABIT SWITCH

HARDWARE FEATURES

Standards and Protocols

IEEE 802.3i, IEEE 802.3u, IEEE 802.3ab , IEEE 802.3x

Interface

16 10/100/1000Mbps RJ45 Ports (Auto Negotiation/Auto MDI/MDIX)

Network Media

10BASE-T: UTP category 3, 4, 5 cable (maximum 100m)

100BASE-TX/1000BASE-T: UTP category 5, 5e or above cable (maximum 100m)

Fan Quantity : Fanless

Physical Security Lock : No

Power Supply : 100-240VAC, 50/60Hz

Power Consumption : Maximum: 9.26W (220V/50Hz)

Max Power Consumption : 9.26W(220V/50Hz)

Max Heat Dissipation : 31.60BTU/h

PERFORMANCE

Switching Capacity : 32Gbps

Packet Forwarding Rate : 23.8Mpps

Warranty: 1 year

8. 24 PORT GIGABIT SWITCH

HARDWARE FEATURES

Standards and Protocols

IEEE 802.3i, IEEE 802.3u, IEEE 802.3ab , IEEE 802.3x

Interface

24 10/100/1000Mbps RJ45 Ports (Auto Negotiation/Auto MDI/MDIX)

Network Media

10BASE-T: UTP category 3, 4, 5 cable (maximum 100m)

100BASE-TX/1000BASE-T: UTP category 5, 5e or above cable (maximum 100m)

Fan Quantity : Fanless

Physical Security Lock : No

Power Supply : 100-240VAC, 50/60Hz

Power Consumption : Maximum: 13.1W (220V/50Hz)

Mounting

Rack Mountable

Max Power Consumption

13.08W(220V/50Hz)

Max Heat Dissipation

44.63BTU/h

PERFORMANCE

Switching Capacity : 48Gbps

Packet Forwarding Rate : 35.7Mpps

Warranty: 1 year

9. 24-PORT MANAGED GIGABIT POE+ SWITCH

Ports:

(24) RJ-45 autosensing 10/100/1000 ports

Supports a maximum of 24 autosensing 10/100/1000 ports

Memory and processor

1 MB flash

Packet buffer size: 512 KB

Latency

100 Mb Latency: < 8 μ s

1000 Mb Latency: < 16 μ s

Throughput up to 35.7 Mpps

Switching capacity 48 Gbps

PoE capability 124 W PoE+

Input voltage 100 - 240 VAC, rated

Power Consumption 160 W (maximum)

Warranty: 1 year

TECHNICAL SPECIFICATION

SPECIFICATIONS

1. INDOOR ACCESS POINT

Wireless

Number of Antennas : 2

WLAN Mode : Wi-Fi 5 (802.11ac)

Antenna Gain : 3 dBi

Transmit Power : 20 dBm

Ports : 1 x 10/100/1000 Mb/s Gigabit Ethernet (RJ45)

Wireless Security : WEP, WPA, AES, TKIP

Supported Clients : 200

Throughput

2.4 GHz: 450 Mb/s

5 GHz: 1300 Mb/s

Supported IEEE Standards : 802.11i

Electrical

DC Input Power : 24 VDC at 0.5 A

Power Consumption : 6.5 W

Warranty: 1 Year

2. 625 VA BACK - UPS

Output Power Capacity : 325 Watts / 625 VA

Max Configurable Power : 325 Watts / 0 VA

Nominal Output Voltage : 230V

Efficiency at Full Load : 65.3%

Topology: Standby

Waveform Type : Square wave

Output Connections

3) Universal Receptacle (Battery Backup)

Efficiency at Half Load : 75.8%

Input : Nominal Input Voltage 230V

Input Frequency : 45 - 65 Hz

Input Connections

IEC-320 C14

Maximum Input Current : 3A

Type of Input Protection Required : 3-pole breaker

Batteries & Runtime

Battery Type : Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof

Typical recharge time 6 hour(s)
Surge Protection and Filtering
Surge energy rating : 273 Joules
With power adapter included
Conformance
Warranty: 2 years repair / replacement

3. WIRELESS PRINTSERVER PRINTER CONNECTION

USB 1.1 (compatible with USB 2.0)
Peer-to-Peer (PTP), Windows LPD printing

Frequency

2.412 ~ 2.462 GHz (US)

Encryption

40-bit (also called 64-bit), 128-bit WEP encryption

WPA-PSK

Network Connection

4-Port Switched Ethernet 10/100 autosensing RJ-45 ports

Wireless

Warranty: 1 Year

4. USB HEADSET WITH NOISE CANCELLING MIC

TECHNICAL SPECIFICATIONS

Input Impedance: 32 Ohms

Sensitivity (headphone): 94dBV/Pa +/- 3 dB

Sensitivity (microphone): -17 dBV/Pa +/- 4 dB

Frequency response (Headset): 20 Hz - 20 kHz

Frequency response (Microphone): 100 Hz -10 kHz

Cable length: 7.64 ft (2.33m)

Connections: USB-A compatible (1.1, 2.0, 3.0)

Warranty: 1 Year

5. 8 TB EXTERNAL HARDDRIVE

Storage capacity: 8TB

Connection: USB 3.0

Hard drive size: 3.5 inches

Max transfer rate: 160MB/s

Ports: 1 x Micro-USB 3.0 (Micro-B 10-pin) Port

2 x USB 3.0 Type-A Ports

Up to 160 MB/s Data Transfer Speed

Warranty: minimum 1 year