

BIODIVERSITY MANAGEMENT BUREAU

Quezon Avenue, Diliman, Quezon City
Telefax No. 924-6031 local 220

Date: **5 Nov 21**
Quotation No: **0381-11-21**

REQUEST FOR QUOTATION

Company Name _____

Address _____

Please quote your lowest price on the item/s listed below, stating the shortest time of delivery and submit your quotation duly signed by your representative not later than _____.


NANCY R. CORPUZ
 Chairperson/ Bids and Awards Committee

- NOTES: 1. ALL ENTRIES MUST BE TYPEWRITTEN OR PRINTED LEGIBLY.
 2. DELIVERY PERIOD IS WITHIN 15 CALENDAR DAYS.
 3. WARRANTY SHALL BE FOR A PERIOD OF SIX (6) MONTHS FOR SUPPLIES & MATERIALS/ONE (1) YEAR FOR EQUIPMENT, FROM DATE OF ACCEPTANCE BY THE PROCURING ENTITY.
 4. PRICE VALIDITY SHALL BE VALID FOR A PERIOD OF 30 CALENDAR DAYS.
 5. PHIL-GEPS REGISTRATION CERTIFICATE SHALL BE ATTACHED UPON SUBMISSION OF THE QUOTATION.
 6. BIDDERS SHALL SUBMIT ORIGINAL BROCHURES SHOWING CERTIFICATIONS OF THE PRODUCT BEING OFFERED.

Title of Procurement: Supply and Delivery of Hard Disk Drives, KVM Switch, and Ethernet Surge Protector
Purpose: For official use of BMB (Server Upgrade and Power Surge Protection)
Approved Budget for the Contract (ABC): P 290,000.00

ITEM NO.	ITEMS/DESCRIPTIONS	QTY./ UNIT	UNIT PRICE	TOTAL PRICE
1	Hard Disk Drive <i>Specifications:</i> Compatible with Lenovo Systems x3650 M5 Capacity: 1.2 TB Internal storage connectivity: 12Gbps, 2.5 inches Generation: G3HS	10 pcs	P _____	P _____
2	Hard Disk Drive <i>Specifications:</i> Compatible with Lenovo Systems x3250 M6 Capacity: 600 GB Internal storage connectivity: 12Gbps, 2.5 inches Generation: G3HS SAS: 10K	4 pcs	P _____	P _____
3	8 Port KVM Switch <i>Specifications:</i> With extension switcher With 8 KVM cables	2 pcs	P _____	P _____
4	Ethernet Surge Protector <i>Specifications:</i> Outdoor/Indoor Devices	20 pcs	P _____	P _____
			TOTAL :	P _____
<p><i>* Kindly address all proposals to the Chairperson, Bids and Awards Committee</i></p> <p>Additional Requests from Procuring Entity: <input type="checkbox"/> Please provide sample upon request of end-user <input checked="" type="checkbox"/> Please see full specifications/attached sample design for reference. <input checked="" type="checkbox"/> Other conditions to this request, please state: For inquiries, please contact the end-user thru: 8924-6031 loc. 253/226</p> <p>Contract shall be awarded to the bidder per: <input type="checkbox"/> Item basis <input checked="" type="checkbox"/> Lot basis</p> <p>Bidders must submit the following requirements:*</p> <ol style="list-style-type: none"> DTI/SEC Registration Certificate Mayor's Permit PHILGEPS Certificate of Registration BIR Certificate of Registration (2303) Omnibus Sworn Statement <p><small>Important Note: - For goods, conforme of the winning bidder must be done within seven (7) calendar days upon serving of the PO. - For services, conforme of the winning bidder must be done within fourteen (14) calendar days upon serving of the JO. - Notarization of the OSS should be complied with after the award of the contract or PO/JO but before payment pursuant to item 6.3 of GPPB 09-2020.</small></p> <p><small>*Non-submission of these requirements may be grounds for disqualification from the bidding process.</small></p>				

Brand : _____
 Delivery Period : _____
 Warranty : _____
 Price Validity : _____

After having carefully read and accepted your Request for Quotation, I/We quote you on the item at prices noted above.

Printed Name/Signature _____

Tel. No./Cellphone No. _____

Email Address _____

Date _____

8-Port KVM Switch USB Wired with Remote Extension Technical Specifications:

- One USB K&M console controls eight computers
- 4 USB 2.0 for keyboard, mouse, printer, flash drive, etc.
- Support wireless Keyboard & Mouse combo.
- Multiple OS support – Windows, Mac, Linux and Sun
- With 2m wire remote switcher, press key to select PC
- Superior video quality - up to 1920 x 1440; DDC2B
- USB-powered

ETHERNET SURGE PROTECTOR Technical Specification

Outdoor Unit

Dimensions 91 x 61 x 32.5 mm
(3.58 x 2.4 x 1.28")

Weight 80 g
(2.82 oz)

Interface Connections (2) RJ45 Female Connectors

ESD/EMP Protection Absorbing Transient Current with Response to
Surge Voltage from 100V/s to 1kV/ μ s

DC Spark-Over Voltage 90V @ 100V/s

Maximum Impulse Spark-Over Voltage 700V @ 1kV/ μ s

Discharge Current 10kA+

Maximum Insulation Resistance 1G ohm @ 50V

Maximum Capacitance 1.0 pF @ 1 MHz

Data Line Protection RJ45 10/100/1000 Ethernet

IEEE 802.3af PoE Support Yes

Shock and Vibration Certification ETSI300-019-1.4 Standard

Operating Temperature -30 to 65° C

(-22 to 149° F)

Operating Humidity 10 to 90% Noncondensing

Indoor Unit

Dimensions 91 x 61 x 32.5 mm
(3.58 x 2.4 x 1.28")

Weight 80 g
(2.82 oz)

Interface Connections (2) RJ45 Female Connectors

ESD/EMP Protection Absorbing Transient Current with Response to
Surge Voltage from 100V/s to 1kV/ μ s

DC Spark-Over Voltage 90V @ 100V/s

Maximum Impulse Spark-over Voltage 700V @ 1kV/ μ s

Discharge Current 5kA (Maximum)

0.5kA (Normal)

Maximum Insulation Resistance 1G ohm @ 50V

Maximum Capacitance 1.0 pF @ 1 MHz

Data Line Protection RJ45 10/100/1000 Ethernet
IEEE 802.3af PoE Support Yes
Shock and Vibration Certification ETSI300-019-1.4 Standard
Operating Temperature -30 to 65° C
(-22 to 149° F)
Operating Humidity 10 to 90% Nonco