BIODIVERSITY MANAGEMENT BUREAU

Quezon Avenue, Diliman, Quezon City Telefax No. 924-6031 local 220

Date: **Quotation No:** PR No.

10 Oct 23 0496-10-23 1023.016

REQUEST FOR QUOTATION

Company Name Address

> Please quote your lowest price on the item/s listed below, stating the shortest time of delivery and submit your quotation duly signed by your representative not later than

> > airperson, Bids and s Committee

- 1. ALL ENTRIES MUST BE TYPEWRITTEN OR PRINTED LEGIBLY.
 2. DELIVERY PERIOD IS WITHIN 15 CALENDAR DAYS.
 3. WARRANTY SHALL BE FOR A PERIOD OF SIX (6) MONTHS FOR SUPPLIES & MATERIALS/ONE (1) YEAR FOR EQUIPMENT, FROM DATE OF ACCEPTANCE BY THE PROCURING ENTITY.
 4. PRICE VALIDITY SHALL BE VALID FOR A PERIOD OF 30 CALENDAR DAYS.
 5. PHIL-GEPS REGISTRATION CERTIFICATE SHALL BE ATTACHED UPON SUBMISSION OF THE QUOTATION.
 6. BIDDERS SHALL SUBMIT ORIGINAL BROCHURES SHOWING CERTIFICATIONS OF THE PRODUCT BEING OFFERED.

Title of Procurement:

Supply and Delivery of I.T equipment (e.g. wall mounted 4u data / server rack and 16 port gigabit ethernet rackmount etc.)

Purpose:

For official use of the Internet connection at Bulwagan Ninoy Aquino Building

Approved Budget for the Contract (ABC):

P55,000.00

Page1 of 2

EM IO.	ITEMS/DESCRIPTIONS	QTY./ UNIT	UNIT PRICE	TOTAL PRICE
	Wall-mounted 4u Data/Server Rack (self assembly) Details: Glass Front panel with key 1 Exhaust slot mounting Type: Wall mounted with 1 fixed tray Removable side panel Dimensio: L530 x W400 x H240mm	1 pc	P	P
2	16 Port Gigabit Ethernet Rackmount Network Switch Hardware Features: Standards and Protocols IEEE 802.3i, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3x Inferface 16 10/100/1000Mbps RJ45 Ports (Auto negotiation / Auto MDI/MDIX) Network Media 10BASE-T: UTP category 3,4,5 cable (maximum 100m) 100BASE-TX/1000BASE-T: UTP category 5, 5e or above cable (maximum 100m) Fan Quality: Fanless Physical Security Lock: No Power supply: 100-240VAC, 50/60Hz Power consumption: 9.26W (220V/50Hz) Max power consumption: 9.26W (220V/50Hz) Max power consumption: 31.60BTU/h PERFORMANCE Switching Capacity: 32Gpbs Packet Forwarding rate: 23.8Mpps Warranty: 1 year	2 pcs	P	P
	1200VA-650W Uninterruptible Power Supply Technical Specification Output Capacity: 1200VA/650W Output (on battery): 220V-240V, 50/60Hz +/- 1Hz Input power: 200V-240V, 50/60Hz +/- 5Hz (auto sensing) Surge: 273 J Battery recharge time: 8 hours No. of outlets: 5-4 universal, 1 IEC 60320 C13 Dimensio: 39 x 19 x 14 cm Battery type: Lead-acid Product warranty 2 years parts and service	1 pc	P	P

Delivery Period	1
Warranty	:
Price Validity	

After having carefully read and accepted your Request for Quotation, I/We quote you on the item at prices noted above.

Printed Name/Signature

Tel. No./Cellphone No.

Email Address

Date

BIODIVERSITY MANAGEMENT BUREAU

Quezon Avenue, Diliman, Quezon City Telefax No. 924-6031 local 220

> Date: Quotation No:

10 Oct 23

PR No.

0496-10-23 1023.016

REQUEST FOR QUOTATION

Company Name Address

> Please quote your lowest price on the item/s listed below, stating the shortest time of delivery and submit your quotation duly signed by your representative not later than

> > ANSON M. TA Chairperson, Bids and ds Committee

NOTES: 1. ALL ENTRIES MUST BE TYPEWRITTEN OR PRINTED LEGIBLY.
2. DELIVERY PERIOD IS WITHIN 15 CALENDAR DAYS.
3. WARRANTY SHALL BE FOR A PERIOD OF SIX (6) MONTHS FOR SUPPLIES & MATERIALS/ONE (1) YEAR FOR EQUIPMENT, FROM DATE OF ACCEPTANCE BY THE PROCURING ENTITY.
4. PRICE VALIDITY SHALL BE VALID FOR A PERIOD OF 30 CALENDAR DAYS.
5. PHIL-GEPS REGISTRATION CERTIFICATE SHALL BE ATTACHED UPON SUBMISSION OF THE QUOTATION.
6. BIDDERS SHALL SUBMIT ORIGINAL BROCHURES SHOWING CERTIFICATIONS OF THE PRODUCT BEING OFFERED.

Title of Procurement:

Supply and Delivery of I.T equipment (e.g. wall mounted 4u data / server rack and 16 port gigabit ethernet rackmount etc.)

Purpose:

For official use of the Internet connection at Bulwagan Ninoy Aquino Building

Approved Budget for the Contract (ABC):

P55 000 00

O.	ITEMS/DESCRIPTIONS	QTY./ UNIT	UNIT PRICE	TOTAL PRICE
4	Indoor Dual-Band POE+ WiFi Access Point Hardware:	2 pcs	P	P
	Networking Interface: (2) 10/100/1000 Ethernet ports: (2) 10/100/1000 Ethernet Ports: (1) USB 2.0			
	Button: Reset Antennas: (3) dual-band antennas			
	2GHz 3 dBi			
	5GHz 3 dBi			
	Max. TX power: 22 dBm Power Method: passive PoE (48V), PoE+ Supported			
- 1	Power Supply: 48V, 0.5A PoE Gigabit Adapter (included)			
	Supported Voltage Range: 44 to 57VDC Maximum Power consumption: 9W			
	Mounting: wall/ceiling (kits included)			
1	Software			
	WiFi Standards: 802.11 a/b/g/n/ac			
	Wireless Security: WEP, WPA-PSK, WPA-Enterprise (WPA/WPA2, TKIP/AES) BSSID: up to four per radio			
1	Advanced QoS: Per-user rate limiting			
1	Guest Traffic Isolation: Supported			
	Power Save" Supported Concurrent Clients: 125+			
	Warranty: 1 year			
	UTP cable Cat5e/300m	1 box	Р	_
- 1	Technical Specification:	1 DOX	P	P
	Number of pairs: 4			
	Total number of conductors: 8 AWG: 24			
	Stranding: solid			
- 1	_AN cable Cat 5e			
1	305 meters / 1000ft			
1	Additional Requests from Procuring Entity.			
1] Please provide sample upon request of end-user			
] Please see full specifications/attached sample design for reference. XI Other conditions to this request, please state:		GRAN TOTAL:	P
	For more info, please contact the end-user at 8924-6031 loc. 226/253			
	Kindly address all proposals to the Chairperson, Bids and Awards Committee Contract shall be awarded to the bidder per.			
] Item basis X] Lot basis			
E n	Bidders must submit the following requirements upon submission of proposal. Non-submission of these equirements shall be grounds for disqualification from the bidding process;			
	DTI/SEC Registration Certificate Valid and Current Mayor's Permit			
	3. PHILGEPS Certificate of Registration			
	BIR Certificate of Registration Sign Omnibus Sworn Statement			
	portant Note:			
	or goods, conforme of the vinning bidder must be done within seven (?) calendar days upon serving of the PO. or services, conforme of the winning bidder must be done within fourteen (14) calendar days upon serving of the JO. otarization of the OSS should be compiled with after the award of the contract but before payment pursuant to item 6.3 of GPP8 09-2020			
	contract but the Coo strong per complied with after the sward of the scattest but before contract but before the		1	

Brand	:	
Delivery Period		
Warranty	:	
Price Validity	:	
Warranty		

After having carefully read and accepted your Request for Quotation, I/We quote you on the item at prices noted above.

Tel. No./Cellphone No. Printed Name/Signature

Email Address

Date

TECHNICAL SPECIFICATION

1. Data Cabinet Rack 4U

Details:

Glass Front Panel with Key 1 Exhaust Slot Mounting Type: Wall Mounted

With 1 fixed tray
Removable Side Panel

Dimension: L530xW400xH240mm

2. 16 PORT GIGABIT SWITCH

HARDWARE FEATURES

Standards and Protocols

IEEE 802.3i, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3x

Interface

16 10/100/1000Mbps RJ45 Ports (Auto Negotiation/Auto MDI/MDIX)

Network Media

10BASE-T: UTP category 3, 4, 5 cable (maximum 100m)

100BASE-TX/1000BASE-T: UTP category 5, 5e or above cable (maximum 100m)

Fan Quantity : Fanless Physical Security Lock : No

Power Supply: 100-240VAC, 50/60Hz

Power Consumption: Maximum: 9.26W (220V/50Hz)

Max Power Consumption: 9.26W(220V/50Hz)

Max Heat Dissipation: 31.60BTU/h

PERFORMANCE

Switching Capacity: 32Gbps

Packet Forwarding Rate: 23.8Mpps

Warranty: 1 year

3. 1200VA-650W Uninterruptible Power Supply

Output Capacity: 1200VA/650W

Output (on battery): 220V-240V, 50/60Hz +/- 1Hz

Input Power: 220V-240V, 50/60Hz +/- 5Hz (auto sensing)

Surge: 273 J

Battery recharge time: 8 hours

No. of Outlets: 5 - 4 universal, 1 IEC 60320 C13

Dimension: 39 x 19 x 14 cm Battery Type: Lead-Acid

Product Warranty

2 Years Parts and Service

1 Year Battery

4. INDOOR ACCESS POINT

Hardware

Networking Interface: (2) 10/100/1000 Ethernet Ports: (2) 10/100/1000 Ethernet

Ports: (1) USB 2.0 Button: Reset

Antennas: (3) Dual-Band Antennas

2 GHz 3 dBi 5 GHz 3 dBi

Max. TX Power: 22 dBm

Power Method: Passive PoE (48V), PoE+ Supported

Power Supply: 48V, 0.5A PoE Gigabit Adapter (Included)*

Supported Voltage Range: 44 to 57VDC Maximum Power Consumption: 9W Mounting: Wall/Ceiling (Kits Included)

Software

WiFi Standards: 802.11 a/b/g/n/ac

Wireless Security: WEP, WPA-PSK, WPA-Enterprise (WPA/WPA2, TKIP/AES)

BSSID: Up to Four per Radio

Advanced QoS: Per-User Rate Limiting Guest Traffic Isolation: Supported

Power Save : Supported Concurrent Clients : 125+

Warranty: 1 year

5. UTP CABLE CAT 5E

Number of Pairs: 4

Total Number of Conductors: 8

AWG: 24

Stranding: Solid LAN Cable Cat 5e 305 meters / 1000ft